

KEY

| |
|--|
| TILE 1ST BRICK 1ST PYROBAR 1ST |
| ADOBE |
| HEIGHT OF BUILDING IN FEET FROM GROUND TO ROOF LINE |
| (C. B.) |
| (C. B.) |
| (CONC.) |
| (TILE) |
| NUMBER OF STORIES |
| TWO STORIES AND BSMT 2/2 COMPOSITION ROOF |
| SHINGLE ROOF X |
| (VEND) |
| BRICK 1ST |
| FRAME, BRICK LINED |
| F=FLAT S=STORE |
| D=DWELLING |
| A IN B AUTO IN BSMT |
| LOFT |
| (ASB. CL.) |
| NON COMBUSTIBLE ROOF COVERING OF METAL, SLATE, TILE OR ASBESTOS SHINGLES |
| SKYLIGHT LIGHTING TOP STORY ONLY |
| 3 SKYLIGHT LIGHTING THREE STORIES |
| W.G. WIRED GLASS SKYLIGHT |
| FIRE WALL 48 INCHES ABV. ROOF |
| 2345 6 |
| W.T. WATER TANK |
| BRICK 1ST |
| A |
| (C. B.) |
| (C. B. & BR.) |
| (C. B. & BR. CONSTN) |
| (C. B. & BR. CONSTN) (BR. FACED) |
| (C. B. & BR. CONSTN) |

Fire proof construction. (OR FIRE RESISTIVE CONSTN)

Adobe building.

Stone building.

Concrete, lime, cinder or cement brick

Hollow concrete or cement block constn

Concrete or reinforced concrete constn

Tile building.

Brick building with frame cornice.

" " " stone front.
" " " frame side.
(DIVIDED BY FRAME PARTITION)

Brick veneered building.

" and frame building.

Frame building, brick lined.

" " metal clad.

Frame residential building

Iron building.

Tenant building occupied by various manufacturing or occupancies

Frame building covered with asbestos

Brick building with brick or metal cornice.

Fire wall 6 inches above roof.

" " " 12 " " "

" " " 18 " " "

" " " 36 " " "

Figures 8, 12, 16 indicate thickness of wall in inches.

Wall without opening and size in inches.

Wall with openings on floors as designated.

Opening with single iron or tin clad door.

" " double iron " " doors.

" " standard fire doors.

Openings with wired glass doors.

Drive or passage way.

Stable.


Auto. House or private garage.

Solid brick with interior walls of C. B. or C. B. and brick mixed.

Mixed construction of C. B. and brick with one wall of solid brick.

Mixed construction of C. B. and brick with one wall faced with 4" brick.

Mixed construction of C. B. and brick throughout.



Open elevator.

Frame enclosed elevator.

" " " with traps.

" " " self closing traps.

Concrete block enclosed elevator with traps.

Tile enclosed elevator with self closing traps.

Brick enclosed elev. with wired glass door.

Window opening in first story.

Window openings in second and third stories.


Window openings in second and fourth stories.

Windows with wired glass.

Windows with iron or tin clad shutters.

Window openings tenth to

twenty-second stories.



- K.P. Vertical pipe or stand pipe.
- AFA Automatic fire alarm.
- IEP Independent electric plant.
- AS Automatic sprinklers.
- ACS Automatic chemical sprinklers.
- AS Automatic sprinklers in part of building only. (NOTE UNDER SYMBOL INDICATES PROTECTED PORTION OF BUILDING)
- NS Not sprinklered.
- Outside vertical pipe on fire escape.
- FA Fire alarm box.
- Single hydrant.
- D.H. Double "
- T.H. Triple "
- Q.H. Quadruple hydrant of the "High Pressure Fire Service".
- H.P.F.S. Fire alarm box of the "High Pressure Fire Service".
- H.P.F.S. Water pipes of the "High Pressure Fire Service"
- + "12" " and hydrants of the "High Pressure Fire Service" as shown on key map.
- 6" W.P.I.P.E. Water pipes and size in inches.
- 6" W.P.I.P.E. (PRIVATE) Water pipes of private supply
- 2 House numbers shown nearest to buildings are official or actually up on buildings.
- D 4/5 Official house numbers shown furthest from buildings.
- Official house numbers shown furthest from buildings.

5 Block number.

UP.B. Vertical steam boiler.

G.T. Gasoline tank.

(O.U.) Open under

Siamese fire dept. connection

Single fire dept. connection

24 Reference to adjoining page.

+ Fire engine house, as shown on key map.

● Fire pump.

(36) Under page number refers to corresponding page of previous edition.